TIS.1195-2536

Professional Pre-Amplifier Series
3D Surround Pre Karaoke

PRODUCT
SK-202



SPECIFICATION : SK-202

Frequency Response	Mic. Input..... 70 Hz. -15 kHz. 0--3 dB.
	Line Input..... 20 Hz. -40 kHz. 0--3 dB.
Distortion(THD) at 1 kHz.	@ +20 dB Max Volume & Master
	Mic.....Better than 0.03%, Line.....Better than 0.002%
Tone Control.	Mic.+/-10 dB. Shelving .....LF 150 Hz., ...HF 8 kHz
	Line+/-10 dB. Shelving.....Bass 100 Hz., Treble 12 kHz.
Noise Measured 20Hz.-20kHz. EIN	Mic./Line Input Ref 150R.....<-123 dBU
Common Mode Rejection Ratio	Mic./Input.....>50 dB.
Hum & Noise	20 Hz.-20 kHz.
Subwoofer Output	@ 125 Hz. 12 dB/Oct.
Max Volume&Boost Disconnec Input	Mic.....<-40 dBU, Line.....<-60 dBU.
GAIN Ref.Pre Out.Max Volume & Master	Mic Input.....+55 dB., Line Input.....+15 dB.
Maximun Input Level	Mic. Input.....-20.5 dBV.., Line Input.....+18 dBV.
Input Impedance	Mic. Input.....>2k Ohms., Line Input.....>40k Ohms.
	Echo Delay Time Control.200-450 mS.
Output Impedance	Pre Output.....>100 Ohm
Dimention(WxHxD)	480 x 50 x 160 mm.
Weight	2 Kgs.
Power Requiremen	220 VAC. 10 VA.

หาซื้อได้ที่ตัวแทนจำหน่ายทั่วประเทศ

Note : Specification and design subject Modification without notce